

BS TRANS H

1° STRUCTURE

CARRIER	NON-WOVEN
LINER	BROWN GLASSINE SILICONE PAPER
ADHESIVE	SYNTHETIC RUBBER
TOTAL THICKNESS	0.10 mm

2° ADHESIVE PROPERTIES

		M.U.	METHOD
ADHESION ON STEEL (Open Side)	27.5	N/25mm	PSTC 101
ADHESION ON STEEL (Closed Side)	25	N/25mm	PSTC 101
TENSILE STRENGTH AT BREAK	25	N/25mm	PSTC 131
ELONGATION AT BREAK	5	%	PSTC 131
TEMPERATURE RESISTANCE	60	°C	-

3° APPLICATIONS

Double-sided adhesive tape particularly suitable for fixing materials even with difficult surfaces, including cartons, metals, felts and plastic materials. Easy to use.

4° CHARACTERISTICS

Synthetic rubber adhesive and resins	High adhesion and adhesiveness on both sides
	Performing on different materials and surfaces
Backing in non-woven	High conformability
	Easily lacerable by hand

5° RECOMMENDATIONS

- Storage**
 For a proper storage of the product we recommend to keep the product in the original package until it is needed and use it within 12 months from delivery.
 The storage shall be carried out at a room temperature between 15°C and 27°C, and a relative humidity < 60%.
 Once removed from the packaging, place the product vertically and protect it from dust. Do not expose product and packaging to direct sunlight and heat sources.
- Surface cleaning**
 The product shall be applied on sufficiently flat surfaces and with no non-stick coating.
 In order to obtain a correct product adhesion level on surfaces, it is indispensable that the surfaces are properly cleaned before the application. It is recommended to use quick-evaporating solvents.
 After cleaning make sure that the solvent has completely evaporated, by waiting for a sufficiently long period of time or by drying the surface with a completely dry cloth.
- Application**
 As adhesive tape is pressure-sensitive, it is necessary a proper pressing pressure on the back of the tape, once applied on the surface, to ensure the grip of the adhesive and a full lamination.
- Measuring tolerances**
 The tape cutting width tolerance can vary within a range of ± 0.7 mm.
 Tighter tolerances for specific formats and measures can be available on request
- Disposal**
 It is recommend to dispose the product after use according to the specific regulations of the country it was used in.

Note: All above information are believed to be true and reliable but they are given only for guidance. They do not constitute a warranty or a specification. The characteristics refer to average values, relevant to samples collected from our production. Users must confirm the suitability of the products through their own tests. BiesSse Tape reserve the right to introduce at any moment and without warning those changes that they deem necessary. Tolerance of Technical Data: $\pm 30\%$