

# Premix

Solvent additive for nylosolv<sup>®</sup> A

## Product features

- Ideal for high quality processing of conventional and digital photopolymer printing plates
- Fast and efficient washout solvent for safe processing of photopolymer printing plates
  - Faster washout time
  - Less plate swelling
  - Less drying time
  - Improved safety in transit and in storage
  - High flashpoint allows washout at higher temperatures
- Easy distillation under vacuum
- Low odour for comfortable work

## Safety and technical information\*

Optimal washout temperature	35 °C 95 °F
Flashpoint	> 62 °C > 144 °F
Transport and Storage	See material safety data sheet
Ignition temperature (approx.)	200 °C 392 °F
Density (approx.=	0.9 g/cm <sup>3</sup> (20 °C   68 °F)
Packing Unit	30 l/can 200 l/barrel

**Please contact us for additional information.**

**Flint Group**, Sieglestr. 25, 70469 Stuttgart, Germany • T +49 711 9816 389 • [info.flexo@flintgrp.com](mailto:info.flexo@flintgrp.com) • [www.flintgrp.com](http://www.flintgrp.com)

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted. Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH). Rely on us<sup>SM</sup> is a service mark of Flint Group.